

RCPTD

DINI ARGEO DIGITAL COLUMN LOAD CELL "RCPTD" SERIES





Digital <u>column load cells</u> ideal for approved CE-M weighbridges or silos and tanks.

CAPACITIES (kg): 30000.

OIML R60. C4 precision class.

Special alloy steel body with **STAINLESS** steel external casing; manufactured with laser solderings. **IP68** protection.


MAIN FEATURES

- AVAILABLE FOR 3590E TOUCH SCREEN INDICATOR.
- C4 PRECISION CLASS.
- SPECIAL ALLOY STEEL BODY with STAINLESS STEEL EXTERNAL CASING; LASER SOLDERINGS.
- IP68 PROTECTION RATING.
- CAPACITY 30000Kg.
- SHIELDED 18m CONNECTION CABLE.
- TEST CERTIFICATE AVAILABLE UPON REQUEST.
- APPROVED WITH 3590 TOUCH SCREEN INDICATOR FOR LEGAL-FOR-TRADE WEIGHING SYSTEMS.
- FITTED WITH SELF-ALIGNED ARTICULATED JOINTS, SELF-CENTERING PLATES AND PROTECTION WASHER.

TECHNICAL FEATURES

- Resolution for nominal load 60.000d.
- Combined error on nominal load ± 0,01%.
- Operating temperature range -10°C/+40°C.
- Power supply tension from 10 to 18 Vdc.
- Conversion: 24 bit.
- Connection RS485.
- Admissible load: 150% F.S.
- Shielded cable 4 poles, 5mm diameter.

•	<u>Wiring Code</u>	
	Colour	<u>Function</u>
	RED	INPUT +
	BLACK	INPUT -
	GREEN	OUTPUT +
	WHITE	OUTPUT -
	BLACK (THICK)	SHIELD






Technical drawing in mm.

Assembly kit for RCPTDx0C3NC cells.

DETAIL 3



Technical drawing in mm with assembly kit.

VERSIONS

Available versions Max Codice (kg) RCPTD30C4-1 30000





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena • Italy Tel. +39.0536 843418

ING. LUBOMIR RAS

HUSOVA 445 - 66401 - BILOVICE NAD SVITAVOU - CZECH REPUBLIC

Tel. 00420-545227462 Fax. 00420-545227462

rumps@volny.cz

SALES AND TECHNICAL ASSISTANCE SERVICE